

MICROMETER MDH







- > Measuring range: 0-25 mm
- > Digital step: 0.1 µm / 0.5 µm (switchable)
- > Max. permissible error of indication MPE₁: 0.6 μm (DIN EN ISO 3611)
- > Constant measuring force: 7-9 N
- > Absolute rotary sensor
- > Weight: 400 g

Application without heat insulting cover



Application with heat insulting cover





Mitutoyo

Mitutoyo Europe GmbH

Borsigstraße 8-10 41469 Neuss Germany

Tel. +49 (0) 2137-102-0 Fax +49 (0) 2137-102-351

info@mitutoyo.eu www.mitutoyo.eu



Find additional product literature and our product catalogue

www.mitutoyo.eu

Note: Product illustrations are without obligation. Product descriptions, in particular any and all technical specifications, are only binding when explicitly agreed upon.

MITUTOYO and MiCAT are either registered trademarks or trademarks of Mitutoyo Corp. in Japan and/or other countries/regions.

Other product, company and brand names mentioned herein are for identification purposes only and may be the trademarks of their respective holders.

Coordinate Measuring Machines

Vision Measuring Systems

Form Measurement

Optical Measuring

Sensor Systems

Test Equipment and Seismometer

Digital Scale and DRO Systems

Small Tool Instruments and Data Management